Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-119-7989



2a Thread Direction: Right-hand Thread Length: 0.562 inches Fastener Length: Between 0.680 inches and 0.725 inches Head Style: Head Height: Between 0.680 inches and 0.725 inches Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.150 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material: Steel Material Specification: Staej 429 assn standard single material response Surface Treatment: Phosphate Mi-p-16232d, type z, class 2 military specification single treatment response Hiread Series Designator:	Thread Class:
Thread Direction:Right-handThread Length:0.562 inchesFastener Length:Between 0.680 inches and 0.725 inchesHead Style:Head Style:Head Beight:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.4375 inchesHole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sa jat29 assn standard single material responseSurface Treatment:PhosphatePhosphateMil-p-16232d, type z, class 2 military specification single treatment responseThread Streis Designator:	
Right-handRight-handChread Length:0.562 inchesFastener Length:Between 0.680 inches and 0.725 inchesHead Style:HexagonHexagonHead Height:Between 0.150 inches and 0.163 inchesVidth Between Flats:Between 0.428 inches and 0.4375 inchesHerad Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:11Stole Quantity:21Between 0.623 inches and 0.631 inchesHole Quantity:11Between 0.623 inchesHole Quantity:11Between 0.623 inchesHole Quantity:11Between 0.623 inchesHole Quantity:11Between 0.623 inchesBetween 0.623 inchesHole Quantity:11Between 0.623 inchesHole Quantity:11Between 0.623 inchesBetween 0.623 inchesBetween 0.623 inchesHole Quantity:2Between 0.623 inchesBetween 0.623 inchesBetw	
Privad Length: 0.562 inches Fastener Length: Between 0.680 inches and 0.725 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.4375 inches Hele Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 1 Hole Quantity: 1 1 1 Hole Quantity: 1 1 Hole Quantity: 1 1 Hole Quantity: 1 Stool pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification:	
0.562 inchesFastener Length:Between 0.680 inches and 0.725 inchesHead Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.4375 inchesHole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelSteelMaterial:PhosphatePhosphatePhosphateMin-Pi6232d, type z, class 2 military specification single treatment responseFuread Steise Designator:	-
Fastener Length:Between 0.680 inches and 0.725 inchesHead Style:HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.4375 inchesHole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial:SteelMaterial:PhosphatePhosphateHole Treatment Specification:Nit-Pi6232d, type z, class 2 military specification single treatment responseFuread Streise Designator:	-
Between 0.680 inches and 0.725 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material: Phosphate Phosphate Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	
Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	
HexagonHead Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.4375 inchesHole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:11Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Haxagon flatsMaterial:StelStelMaterial Specification:Surface Treatment SpecificationsSurface Treatment SpecificationsMil-p-16232d, type z, class 2 military specification single treatment response	
Head Height:Between 0.150 inches and 0.163 inchesWidth Between Flats:Between 0.428 inches and 0.4375 inchesHole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelSteelMaterial Specification:Surface Treatment:PhosphateSurface Treatment Specification single treatment responseFurface Treatment:Nil-p-16232d, type z, class 2 military specification single treatment responseFurface Specification:Mil-p-16232d, type z, class 2 military specification single treatment response	
Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	-
Width Between Flats: Between 0.428 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	-
Between 0.428 inches and 0.4375 inches Hole Diameter: Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material: Steel Steel Steel Stere Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Hole Diameter:Between 0.623 inches and 0.631 inchesThread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledDrinedy Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Between 0.623 inches and 0.631 inches Thread Diameter: 0.250 inches Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	
Thread Diameter:0.250 inchesHole Quantity:1Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment response	
0.250 inches Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Steel Material Specification: Steel Material Specification: Phosphate Surface Treatment: Phosphate Mil-p-16232d, type z, class 2 military specification single treatment response	
Hole Quantity: 1 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
1Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Hole Type:DrilledThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response	
Thready Qty Per Inch (tpi):28Min. Tensile Strength (psi):5450 pounds per square inchHole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
28 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
 Min. Tensile Strength (psi): 5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator: 	
5450 pounds per square inch Hole Configuration Style: Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Hole Configuration Style:Hexagon flatsMaterial:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Hexagon flats Material: Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Material:SteelMaterial Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Steel Material Specification: Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	-
Material Specification:Sae j429 assn standard single material responseSurface Treatment:PhosphateSurface Treatment Specification:Mil-p-16232d, type z, class 2 military specification single treatment responseThread Series Designator:	
Sae j429 assn standard single material response Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Surface Treatment: Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Phosphate Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Surface Treatment Specification: Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	
Mil-p-16232d, type z, class 2 military specification single treatment response Thread Series Designator:	-
Thread Series Designator:	-
-	Mil-p-16232d, type z, class 2 military specification single treatment response
l la f	Thread Series Designator:
Unt	Unf
Shelf Life:	Shelf Life:
	N/a
N/a	Unit Of Measure:
N/a	Unit Of Measure:

NSN 5305-01-119-7989

Hexagon Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232d spec.