Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-120-4359



| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.477 inches and 0.637 inches |
| Fastener Length: |
| Between 0.767 inches and 0.787 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.360 inches and 0.404 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| 0.156 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 140000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches grip |
| Special Features: |
| Threads to be double lead |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-01-120-4359

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

