

View Online at <https://aerobasegroup.com/nsn/5305-01-120-8167>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.309 inches and 0.406 inches

Fastener Length:

Between 0.359 inches and 0.406 inches

Head Style:

Hexagon

Head Height:

Between 0.049 inches and 0.060 inches

Width Between Flats:

Between 0.181 inches and 0.189 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp e4340 or steel comp 8740

Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.