NSN 5305-01-120-9907



Thumbscrew - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-120-9907 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 2.754 inches and 3.000 inches **Fastener Length:** Between 2.910 inches and 3.000 inches **Head Style:** Thumb no. 3 **Head Height:** Between 0.920 inches and 0.950 inches Width Between Flats: Between 0.800 inches and 0.830 inches **Point Style:** Flat **Thread Diameter:** 0.375 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 16 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate or zinc and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification 1st treatment response or mil-c-81562, type 2, class 3 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Mil otd (military Standard)

No Fiig: A003b0