

View Online at <https://aerobasegroup.com/nsn/5305-01-121-0332>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.107 inches and 1.250 inches

Fastener Length:

Between 1.190 inches and 1.250 inches

Head Style:

Hexagon

Head Height:

Between 0.208 inches and 0.230 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

60000 pounds per square inch

Screw Material:

Steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 or steel comp 1137 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp 1146 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1214 or steel comp 1139

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response or mil-c-81562, type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type and 10s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-81562 spec