Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-121-0337



| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.412 inches and 0.478 inches                                     |
| Fastener Length:  |
| Between 0.547 inches and 0.593 inches                                     |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.283 inches and 0.332 inches                                     |
| Locking Feature:  |
| Pellet threads or strip threads   |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.164 inches  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Min. Tensile Strength (psi):  |
| 125000 pounds per square inch   |
| Hardness Rating:  |
| 26.0 rockwell c and 32.0 rockwell c                                       |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees                                    |
| Material:   |
| Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130  |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A003b0  |
|   |