Socket Head Cap Screw - Page 1 of 2





| Thread Class:  |
|--|
|  |
| 3a<br>Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.477 inches and 0.636 inches  |
| Fastener Length:   |
| Between 1.047 inches and 1.067 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.360 inches and 0.404 inches  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.250 inches   |
| Width Across Flats:  |
| 0.156 inches   |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Min. Tensile Strength (psi):   |
| 140000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Surface Finish:  |
| 32.0 microinches grip  |
| Special Features:  |
| Threads to be double lead  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5732 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

---

## NSN 5305-01-121-0343

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

