NSN 5305-01-121-1648

Between 0.327 inches and 0.375 inches

Between 0.343 inches and 0.375 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Head Style: Pan no. 2

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-121-1648

Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.099 inches and 0.110 inches
Washer Quantity:
2
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
55000 pounds per square inch
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.334 inches
Secondary Washer Outside Diameter:
Between 0.338 inches and 0.348 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.047 inches
Secondary Washer Material Thickness:
·
Between 0.029 inches and 0.035 inches
Between 0.029 inches and 0.035 inches
Between 0.029 inches and 0.035 inches Material:

NSN 5305-01-121-1648

Assembled Washer Screw - Page 2 of 2



Surrace Treatment:
Tin
Surface Treatment Specification:
Qq-n-290 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas720 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0