Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-121-1648



**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.327 inches and 0.375 inches Fastener Length: Between 0.343 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches Washer Quantity: 2 Internal Drive Style: Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch Secondary Washer Relationship To Primary Washer: Not identical Secondary Washer Style: Flat **Primary Washer Outside Diameter:** 0.334 inches Secondary Washer Outside Diameter: Between 0.338 inches and 0.348 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.047 inches **Secondary Washer Material Thickness:** Between 0.029 inches and 0.035 inches Material: Copper alloy 510 primary washer **Material Specification:** 

Qq-p-750, comp a federal specification single material response primary washer

## NSN 5305-01-121-1648

Assembled Washer Screw - Page 2 of 2



Surface Treatment:

Tin

Surface Treatment Specification:

Qq-n-290 federal specification single treatment response

Thread Series Designator:

Unf

**Specification Data:** 

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0