NSN 5305-01-121-2689

Between 0.202 inches and 0.250 inches

Between 0.218 inches and 0.250 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-121-2689

Head Style:
Pan no. 2
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.085 inches and 0.096 inches
Washer Quantity:
2
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
55000 pounds per square inch
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.293 inches
Secondary Washer Outside Diameter:
Between 0.307 inches and 0.317 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.040 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material:
Copper alloy 510 primary washer
Material Specification:
Qq-p-750, comp a federal specification single material response primary washer

NSN 5305-01-121-2689

Assembled Washer Screw - Page 2 of 2



Surface Treatment:
Tin
Surface Treatment Specification:
Qq-n-290 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas720 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0