NSN 5305-01-121-5492

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-121-5492 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 1.335 inches **Head Style:** Flat chamfer **Head Diameter:** 0.463 inches **Head Height:** 0.309 inches **First Diameter From Head:** Between 0.262 inches and 0.267 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.960 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 33.0 rockwell c and 42.0 rockwell c **Externally Relieved Body Diameter Quantity: Chamfer Angle:** Between 30.0 degrees and 45.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-121-5492

Externally Relieved Body Screw - Page 2 of 2



Inread Series Designato
Unrf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0