Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-121-9349

3aThread Direction:Right-handThread Length:0.250 inchesFastener Length:1.000 inchesHead Style:HexagonFirst Diameter From Head:Between 0.172 inches and 0.177 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.620 inchesThread Diameter:0.250 inchesThread Diameter:0.250 inches20
Right-handThread Length:0.250 inchesFastener Length:1.000 inchesHead Style:HexagonFirst Diameter From Head:Between 0.172 inches and 0.177 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.620 inchesThread Diameter:0.250 inchesThread Diameter:0.250 inches
Thread Length: 0.250 inches Fastener Length: 1.000 inches Head Style: Head Style: Hexagon First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches
0.250 inches Fastener Length: 1.000 inches Head Style: Hexagon First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Fastener Length:1.000 inchesHead Style:HexagonFirst Diameter From Head:Between 0.172 inches and 0.177 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.620 inchesThread Diameter:0.250 inchesThready Qty Per Inch (tpi):
1.000 inches Head Style: Hexagon First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Head Style: Hexagon First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches
Hexagon First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
First Diameter From Head: Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Between 0.172 inches and 0.177 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
0.620 inches Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi):
0.250 inches Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0