NSN 5305-01-121-9351

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-121-9351 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.180 inches |
| Fastener Length: |
| 0.500 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.205 inches and 0.219 inches |
| Head Height: |
| Between 0.070 inches and 0.080 inches |
| First Diameter From Head: |
| Between 0.080 inches and 0.085 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.320 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 8000 pounds per square inch |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Stainless steel |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-121-9351

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0