NSN 5305-01-122-4503

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-122-4503 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.225 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.275 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0

NSN 5305-01-122-4503

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.