NSN 5305-01-122-5454

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-122-5454 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.528 inches and 0.620 inches **Fastener Length:** Between 0.590 inches and 0.620 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Head Surface Treatment:** Paint **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Special Features:** Furnished with boot type nylon washer 0.438 in. Od; head and washer color black per federal standard 595 no. 27038 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-122-5454 Machine Screw - Page 2 of 2



Fiig:

A500d0