Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-122-8513

view Online at https://aerobasegroup.com/hsn/5505-01-122-6515
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
1.125 inches
Head Style:
Fillister
Head Diameter:
Between 0.208 inches and 0.226 inches
Head Height:
Between 0.089 inches and 0.096 inches
First Diameter From Head:
0.138 inches
Second Diameter From Head:
0.090 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.190 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.750 inches
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 8630
Material Specification:
Mil-s-6050 military specification single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.