NSN 5305-01-123-4601

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-123-4601

The LOIS
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.380 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Round extended washer
Head Diameter:
0.375 inches
Head Height:
Between 0.089 inches and 0.099 inches
Extended Washer Diameter:
0.437 inches
Extended Washer Thickness:
Between 0.025 inches and 0.030 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Screw Material:
Steel comp 4037 or steel comp 8630
Screw Material Specification:
Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-123-4601

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.