NSN 5305-01-124-3628

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-124-3628 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Locking Feature:** Pellet threads or strip threads or patch threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1191 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-124-3628

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0