

View Online at <https://aerobasegroup.com/nsn/5305-01-124-5764>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.230 inches and 0.310 inches

**Fastener Length:**

Between 0.280 inches and 0.310 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.049 inches and 0.060 inches

**Width Between Flats:**

Between 0.181 inches and 0.189 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Special Features:**

Green dye or paint onthread end

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas6000 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0