## NSN 5305-01-124-5772

**Thread Class:** 

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-124-5772

3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.313 inches and 0.363 inches					
Fastener Length:					
Between 0.385 inches and 0.415 inches					
Head Style:					
Pan					
Head Diameter:					
Between 0.306 inches and 0.322 inches					
Head Height:					
Between 0.105 inches and 0.115 inches					
Locking Feature:					
Pellet threads or strip threads or patch threads					
Grip Diameter:					
Between 0.1625 inches and 0.1635 inches					
Internal Drive Style:					
Offset cruciform (torque set)					
Thread Diameter:					
0.164 inches					
Grip Length:					
Between 0.052 inches and 0.072 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
160000 pounds per square inch					
Surface Finish:					
32.0 microinches threads					
Material:					
Plastic locking feature					
Material Specification:					
Ams 5737 assn standard single material response fastener					
Surface Treatment:					
Passivate fastener					
Surface Treatment Specification:					
Qq-p-35 federal specification single treatment response fastener					
Thread Series Designator:					
Unjc					
Specification Data:					
80205-nas1172 professional/industrial association standard					

## NSN 5305-01-124-5772

Close Tolerance Screw - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0