NSN 5305-01-124-6612

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-124-6612 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.297 inches **Fastener Length:** 0.609 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.094 inches **First Diameter From Head:** Between 0.203 inches and 0.221 inches **Second Diameter From Head:** Between 0.215 inches and 0.225 inches **Third Diameter From Head:** 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.031 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.140 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.220 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-124-6612

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0