## NSN 5305-01-124-7700

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-124-7700 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.160 inches and 0.180 inches **Fastener Length:** Between 4.463 inches and 4.493 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.500 inches **Head Height:** 0.150 inches **Shoulder Diameter:** 0.235 inches first shoulder and 0.245 inches first shoulder **Shoulder Length:** 4.263 inches first shoulder and 4.273 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 302 or steel comp 304 or steel comp 303 **Material Specification:** Aisi assn standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-124-7700

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.