Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-125-1181



#### Thread Class:

2a

**Thread Direction:** 

Right-hand

# Thread Length:

Between 0.419 inches and 0.500 inches

# Fastener Length:

Between 0.469 inches and 0.500 inches

## Head Style:

Dished hexagon

# Head Height:

Between 0.067 inches and 0.080 inches

# Width Between Flats:

Between 0.245 inches and 0.250 inches

# Washer Quantity:

1

#### Internal Drive Style:

W/o internal drive

#### Thread Diameter:

0.138 inches

## Thready Qty Per Inch (tpi):

40

## Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

## Primary Washer Outside Diameter:

Between 0.270 inches and 0.280 inches

#### **Primary Washer Style:**

Flat external teeth

## Primary Washer Material Thickness:

0.016 inches

#### Material:

Steel comp 1050 primary washer or steel comp 1566 primary washer

#### Material Specification:

Sae assn standard 2nd material response primary washer

#### Surface Treatment:

Cadmium primary washer or zinc primary washer

## **Thread Series Designator:**

Unf

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5305-01-125-1181

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

