NSN 5305-01-125-1181

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-125-1181 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.419 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Dished hexagon **Head Height:** Between 0.067 inches and 0.080 inches Width Between Flats: Between 0.245 inches and 0.250 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.270 inches and 0.280 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.016 inches Material: Steel comp 1050 primary washer or steel comp 1566 primary washer **Material Specification:** Sae assn standard 2nd material response primary washer **Surface Treatment:** Cadmium primary washer or zinc primary washer **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-125-1181

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0