## NSN 5305-01-125-1198

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-125-1198



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.283 inches and 0.375 inches

#### Fastener Length:

Between 0.345 inches and 0.375 inches

#### **Head Style:**

Flat chamfer

Head Diameter:

Between 0.303 inches and 0.312 inches

#### **Head Height:**

Between 0.185 inches and 0.190 inches

### Internal Drive Style:

Hexagon

#### Thread Diameter:

0.190 inches

### Width Across Flats:

Between 0.156 inches and 0.159 inches

## Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Iron alloy 660

### Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

### Surface Treatment:

Passivate

### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

### **Thread Series Designator:**

Unrf

#### **Specification Data:**

80205-nas1351 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-125-1198

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

