## NSN 5305-01-125-6208



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-125-6208 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.468 inches and 0.563 inches **Fastener Length:** Between 0.530 inches and 0.563 inches **Head Style: Button Head Diameter:** Between 0.250 inches and 0.262 inches **Head Height:** Between 0.063 inches and 0.073 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.078 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 384 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-125-6208

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0