

NSN 5305-01-126-1194 Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-126-1194 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length:

Between 0.107 inches and 0.123 inches **Fastener Length:** 0.188 inches **Head Style:** 

**Head Diameter:** Between 0.205 inches and 0.219 inches

**Head Height:** Between 0.058 inches and 0.068 inches

Washer Quantity:

Pan no. 2

**Internal Drive Style:** 

**Thread Diameter:** 

0.112 inches

Thready Qty Per Inch (tpi):

**Secondary Washer Relationship To Primary Washer:** 

Not identical

**Secondary Washer Style:** 

Flat

Slot

40

**Primary Washer Outside Diameter:** 

Between 0.124 inches and 0.212 inches

**Secondary Washer Outside Diameter:** 

Between 0.213 inches and 0.223 inches

**Primary Washer Style:** 

Split helical ring

**Primary Washer Material Thickness:** 

Between 0.025 inches and 0.031 inches

**Secondary Washer Material Thickness:** 

Between 0.013 inches and 0.019 inches

**Product Name:** 

Navy special project

Material:

Steel comp 1008 fastener

**Surface Treatment:** 

Cadmium secondary washer

## NSN 5305-01-126-1194

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0