

View Online at <https://aerobasegroup.com/nsn/5305-01-126-4705>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.310 inches and 0.366 inches

**Fastener Length:**

Between 0.360 inches and 0.366 inches

**Head Style:**

Flush

**Head Diameter:**

Between 0.214 inches and 0.220 inches

**Head Height:**

Between 0.038 inches and 0.044 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

64

**Screw Material:**

Steel comp 303 or steel comp 304

**Screw Material Specification:**

Astm a582 assn standard 1st material response or qq-s-763 federal specification 2nd material response

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Special Features:**

Undercut on threads 0.055 in. Min. And 0.060 in. Max. Dia. By 0.055 in. Min. And 0.060 in. Max. Lg. 0.060 in. Min. And 0.076 in. Max. From end

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.