

View Online at <https://aerobasegroup.com/nsn/5305-01-126-4705>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.310 inches and 0.366 inches

Fastener Length:

Between 0.360 inches and 0.366 inches

Head Style:

Flush

Head Diameter:

Between 0.214 inches and 0.220 inches

Head Height:

Between 0.038 inches and 0.044 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

64

Screw Material:

Steel comp 303 or steel comp 304

Screw Material Specification:

Astm a582 assn standard 1st material response or qq-s-763 federal specification 2nd material response

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Special Features:

Undercut on threads 0.055 in. Min. And 0.060 in. Max. Dia. By 0.055 in. Min. And 0.060 in. Max. Lg. 0.060 in. Min. And 0.076 in. Max. From end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.