

View Online at <https://aerobasegroup.com/nsn/5305-01-126-8805>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.790 inches

**Fastener Length:**

1.009 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.198 inches and 0.202 inches

**Shank Unthreaded Hole Diameter:**

0.0390 inches first hole and 0.0405 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.1094 inches and 0.1111 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

30.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.919 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard 1st material response or ams 5643 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 1 or type 2 or type 3 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0