

View Online at <https://aerobasegroup.com/nsn/5305-01-126-8805>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.790 inches

Fastener Length:

1.009 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.198 inches and 0.202 inches

Shank Unthreaded Hole Diameter:

0.0390 inches first hole and 0.0405 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

30.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.919 inches first hole

Surface Finish:

32.0 microinches bearing surface of head

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard 1st material response or ams 5643 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 type 1 or type 2 or type 3 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0