NSN 5305-01-126-8806

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-126-8806 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.421 inches and 0.451 inches **Fastener Length:** Between 0.595 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.311 inches and 0.359 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** 82.0 degrees **Product Name:** Navy special project Material: Steel comp 316 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and mil-c-13924 cl4 military specification 2nd treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-01-126-8806

Socket Head Cap Screw - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.