## NSN 5305-01-126-9396

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.413 inches and 0.463 inches Fastener Length: Between 0.923 inches and 0.953 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.573 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3117 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams-6487 assn standard single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Nas-672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5305-01-126-9396

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

