## NSN 5305-01-127-3754

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-127-3754 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.250 inches **Fastener Length:** Between 0.590 inches and 0.595 inches **Head Style:** Flat chamfer **Head Diameter:** 0.281 inches **Head Height:** Between 0.120 inches and 0.130 inches **Grip Diameter:** Between 0.1892 inches and 0.1894 inches **Shank Unthreaded Hole Diameter:** 0.062 inches first hole and 0.067 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.340 inches and 0.375 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.530 inches first hole and 0.555 inches first hole **Surface Finish:** 63.0 microinches sides of head Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 

Unf

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-127-3754

Close Tolerance Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0