

View Online at <https://aerobasegroup.com/nsn/5305-01-127-3755>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.220 inches and 0.250 inches

**Fastener Length:**

Between 0.800 inches and 0.805 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.281 inches

**Head Height:**

Between 0.120 inches and 0.130 inches

**Grip Diameter:**

Between 0.1870 inches and 0.1872 inches

**Shank Unthreaded Hole Diameter:**

0.062 inches first hole and 0.067 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.550 inches and 0.585 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.710 inches first hole and 0.735 inches first hole

**Surface Finish:**

63.0 microinches sides of head

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0