## NSN 5305-01-127-4198

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-127-4198 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.287 inches **Fastener Length:** 0.850 inches **Head Style:** Fillister **Head Diameter:** 0.226 inches **Head Height:** 0.093 inches **First Diameter From Head:** 0.125 inches **Second Diameter From Head:** 0.095 inches **Third Diameter From Head:** 0.125 inches **Fourth Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.430 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.449 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.563 inches **Internal Drive Style: Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Askewed Head Angle:** 90.0 degrees **Externally Relieved Body Diameter Quantity:** 

Material:

Steel comp 303

## NSN 5305-01-127-4198

Externally Relieved Body Screw - Page 2 of 2



Material Specification
------------------------

Qq-s-764, type 303, cond a federal specification single material response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0