NSN 5305-01-127-4208

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-127-4208 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.256 inches and 0.358 inches **Fastener Length:** Between 0.640 inches and 0.660 inches **Head Style:** Flat countersunk **Head Diameter:** 0.258 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5732 assn standard 1st material response or ams5737 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Special Features:** Three slots equally spaced along longitudinal axis on outside diameters. Length 0.575 in. Width 0.028 in. Min. 0.033 in. Max. **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0