NSN 5305-01-127-7084

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-127-7084

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| Between 1.960 inches and 2.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.218 inches and 0.226 inches |
| Head Height: |
| Between 0.134 inches and 0.138 inches |
| Locking Feature: |
| Strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.138 inches |
| Width Across Flats: |
| Between 0.109 inches and 0.111 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 155000 pounds per square inch |
| Material: |
| Steel fastener |
| Surface Treatment: |
| Cadmium fastener and chromate fastener |
| Surface Treatment Specification: |
| Qq-p-416, type 2 class 2 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unrc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| Specification Or Standard: |
| 0.4 |

6 type

NSN 5305-01-127-7084

Socket Head Cap Screw - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0