## NSN 5305-01-128-1046

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-1046

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.511 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Fillister
Head Diameter:
Between 0.490 inches and 0.518 inches
Head Height:
Between 0.201 inches and 0.211 inches
Hole Diameter:
0.070 inches
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
80000 pounds per square inch
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Screw Material Specification:
66 federal standard all material responses
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unf
Specification Or Standard:
1 type and 5s style
Shelf Life:
N/a

## NSN 5305-01-128-1046

Machine Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0