## NSN 5305-01-128-2916

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-2916

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.314 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.134 inches and 0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
64
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Product Name:
Navy special project
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener

Unrf

**Thread Series Designator:** 

## NSN 5305-01-128-2916

Socket Head Cap Screw - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0