
NSN 5305-01-128-2928

Close Tolerance Screw - Page 1 of 2

3a

28

N/a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.253 inches and 0.303 inches Fastener Length: Between 5.138 inches and 5.168 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.140 inches and 0.150 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 4.865 inches and 4.885 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard Shelf Life:

NSN 5305-01-128-2928

Close Tolerance Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0