NSN 5305-01-128-5123

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-5123 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.682 inches **Fastener Length:** Between 1.687 inches and 1.734 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.756 inches and 0.760 inches **Head Height:** Between 0.115 inches and 0.117 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Furnished with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-128-5123

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0