NSN 5305-01-128-5127

Close Tolerance Screw - Page 1 of 2





| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.630 inches and 0.697 inches |
| Fastener Length: |
| Between 2.015 inches and 2.062 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.881 inches and 0.888 inches |
| Head Height: |
| Between 0.130 inches and 0.133 inches |
| Grip Diameter: |
| Between 0.4365 inches and 0.4370 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Special Features: |
| Furnished with one oring |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-128-5127

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

