NSN 5305-01-128-5656

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-5656 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.836 inches and 0.866 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.551 inches and 0.562 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Primary Washer Outside Diameter:** Between 0.635 inches and 0.651 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.094 inches **Special Features:** Drilled hole in threaded end 0.166 in. Dia, 0.270 ins hole center to end of fastener, used for insertion of nylon pellet Material: Steel **Material Specification:** Ff-b-575 federal specification 1st material response and qq-s-631 federal specification 2nd material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-128-5656

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0