NSN 5305-01-128-6641

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-6641

view Offilite at https://aerobasegroup.com/nsi//3505-01-120-0041
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.500 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.312 inches and 0.316 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-128-6641

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0