## NSN 5305-01-128-6652

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-128-6652

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.303 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.093 inches and 0.095 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, cl 1 military specification single treatment response

## NSN 5305-01-128-6652

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-13924 spec.