NSN 5305-01-128-8155

Machine Screw - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5305-01-128-8155

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.390 inches and 0.421 inches |
| Fastener Length: |
| Between 0.797 inches and 0.844 inches |
| Head Style: |
| Fillister extended washer |
| Head Diameter: |
| 0.375 inches |
| Head Height: |
| Between 0.089 inches and 0.099 inches |
| Extended Washer Diameter: |
| 0.437 inches |
| Extended Washer Thickness: |
| Between 0.025 inches and 0.030 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Screw Material: |
| Steel |
| Screw Material Specification: |
| Mil-s-6050 military specification single material response or ams 6300 assn standard single material response |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5305-01-128-8155

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.