Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-129-0543

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.190 inches

Fastener Length:

0.500 inches

Head Style:

Pan

Head Diameter:

0.210 inches

Head Height:

Between 0.065 inches and 0.085 inches

First Diameter From Head:

0.075 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.310 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

1

Special Features:

Color black

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316l or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

595 no 37038 federal standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

- ---
- Demilitarization:

NSN 5305-01-129-0543

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

