Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-129-0571

3a         3a         Thread Direction:         Right-hand         Thread Length:         1.000 inches         Fastener Length:         Between 2.815 inches and 2.875 inches         Head Style:         Flat chamfer         Head Diameter:         Between 0.365 inches and 0.375 inches         Head Height:         Between 0.365 inches and 0.250 inches         Head Height:         Between 0.244 inches and 0.250 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.250 inches         Vidth Across Flats:         Between 0.250 inches and 0.253 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         180000 pounds per square inch         Hardness Rating:         38.0 rockwell c and 45.0 rockwell c         Minimum Yield Strength:         155000 pounds per square inch         Material:         Steel         Surface Treatment:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response	Thread Class:
Thread Direction:Right-handThread Length:1.000 inchesFastener Length:Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Q-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnfSpecification Data:	
Right-handRight-handThread Length:1.000 inchesFastener Length:Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.365 inches and 0.250 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment Specification:Qu-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	
Thread Length:1.000 inchesFastener Length:Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:03.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateQup-416, ty2 cl2 federal specification single treatment responseThread Streis Designator:UnfSpecification Data:	
1.000 inchesFastener Length:Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Q-p-416, ty2 cl2 federal specification single treatment responseChread Series Designator:UnfSpecification Data:	5
Fastner Length:Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Qap-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnfSpecification Data:	-
Between 2.815 inches and 2.875 inchesHead Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Qap-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	
Head Style:Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Series Designator:UnrfSpecification Data:	-
Flat chamferHead Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Series Designator:UnrfUnrfSpecification Data:	
Head Diameter:Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment:Quep-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	
Between 0.365 inches and 0.375 inchesHead Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateGurface Treatment Specification single treatment responseThread Series Designator:UnrfUnrfSpecification Data:	
Head Height:Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Series Designator:UnrfSpecification Data:	
Between 0.244 inches and 0.250 inchesInternal Drive Style:HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelStrefSurface Treatment:Qap-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	
Internal Drive Style: Hexagon Thread Diameter: 0.250 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf	Head Height:
HexagonThread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseCaq-p-416, ty2 cl2 federal specification single treatment responseUnrfSpecification Data:	Between 0.244 inches and 0.250 inches
Thread Diameter:0.250 inchesWidth Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification single treatment responseThread Series Designator:UnrfSpecification Data:	Internal Drive Style:
0.250 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: 55000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf	Hexagon
Width Across Flats:Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	Thread Diameter:
Between 0.250 inches and 0.253 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	0.250 inches
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Width Across Flats:
28 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Strel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Between 0.250 inches and 0.253 inches
Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	Thready Qty Per Inch (tpi):
<ul> <li>180000 pounds per square inch</li> <li>Hardness Rating:</li> <li>38.0 rockwell c and 45.0 rockwell c</li> <li>Minimum Yield Strength:</li> <li>155000 pounds per square inch</li> <li>Material:</li> <li>Steel</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment Specification:</li> <li>Qq-p-416, ty2 cl2 federal specification single treatment response</li> <li>Thread Series Designator:</li> <li>Unrf</li> <li>Specification Data:</li> </ul>	28
Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Min. Tensile Strength (psi):
38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	180000 pounds per square inch
Minimum Yield Strength: 155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Hardness Rating:
155000 pounds per square inch Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	38.0 rockwell c and 45.0 rockwell c
Material:SteelSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2 cl2 federal specification single treatment responseThread Series Designator:UnrfSpecification Data:	Minimum Yield Strength:
Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	155000 pounds per square inch
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Material:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Steel
Surface Treatment Specification: Qq-p-416, ty2 cl2 federal specification single treatment response Thread Series Designator: Unrf Specification Data:	Surface Treatment:
Qq-p-416, ty2 cl2 federal specification single treatment response <b>Thread Series Designator:</b> Unrf <b>Specification Data:</b>	Cadmium and chromate
Thread Series Designator: Unrf Specification Data:	Surface Treatment Specification:
Unrf Specification Data:	Qq-p-416, ty2 cl2 federal specification single treatment response
Specification Data:	Thread Series Designator:
-	Unrf
80205-nas1351 professional/industrial association standard	Specification Data:
	80205-nas1351 professional/industrial association standard
Shelf Life:	-
N/a	N/a
Unit Of Measure:	Unit Of Measure:

## NSN 5305-01-129-0571

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

