NSN 5305-01-129-2202



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-129-2202 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.445 inches and 0.495 inches **Fastener Length:** Between 1.705 inches and 1.735 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.633 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material:

Titanium alloy **Material Specification:** Nas 621 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas665 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-129-2202

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0